


Inwerter 1-fazowy SGN1300TL

Kod ElektriKo: 97298



UWAGA: Zdjęcie poglądowe dla całej rodziny produktów.

Dane techniczne:

- Moc **1300 W**
- Napięcie [V] **180-270Vdc**
- Wymiary [mm] **380 x 320 x 140 mm**
- Częstotliwość **50 Hz / 60 Hz**
- Waga net. **12 kg**
- Liczba faz w sieci **1 - fazowy**

Maksymalna wydajność 98,0%

Wysoka wydajność w szerokim zakresie działania

Szeroki zakres napięcia wejściowego DC i MPPT

Niskie napięcie DC

Ochrona IP65 przed wodą i pyłem

Przełącznik DC

Model	SGN1300TL	SGN1800TL	SGN2300TL	SGN2700TL	SGN3000TL
Rated AC Power	1000 W	1500 W	2000 W	2500 W	2800 W
Max. AC Power	1100 VA	1650 VA	2200 VA	2500 VA	3080 VA
DC Input					
Max. Input Power	1300 W	1800 W	2300 W	2700 W	3200 W
Max. DC Input Voltage	500 Vdc	500 Vdc	500 Vdc	500 Vdc	500 Vdc
MPPT Operating Voltage Range	50 ~ 450 Vdc	70 ~ 450 Vdc	70 ~ 450 Vdc	70 ~ 450 Vdc	70 ~ 450 Vdc
Startup Voltage	50 Vdc	60 Vdc	60 Vdc	60 Vdc	60 Vdc
Initial Feeding Voltage	60 Vdc	90 Vdc	90 Vdc	90 Vdc	100 Vdc
Max. Input Current	12A	12A	12A	12A	12A
MPPT Number	1	1	1	1	1
Max. Number of PV Strings Per MPPT	1	1	1	1	1
AC Output					
Nominal AC Voltage	220 Vac / 230 Vac / 240 Vac				
AC Connection	L / N / PE				
AC Voltage Range	180 ~ 270 Vac (May vary as per corresponding country' s grid standard)				
AC Frequency Range	50/60 Hz, -5 Hz ... +5 Hz				
Max. Output Current	6 A	8.4 A	11.3 A	12.8 A	15.7 A
Power Factor	> 0.99, 0.8 leading to 0.8 lagging controllable				
THDI	< 1%				
Efficiency					
Max. Efficiency	> 97.1%	> 97.3%	> 97.3%	> 97.5%	> 97.5%
European Efficiency	> 96.5%	> 96.7%	> 96.9%	> 96.9%	> 96.9%
MPPT Efficiency	> 99.9%	> 99.9%	> 99.9%	> 99.9%	> 99.9%
Protection					
Anti-Islanding Protection			Integrated		
DC Reverse Polarity Protection			Integrated		
Insulation Monitoring			Integrated		
AC Over Current Protection			Integrated		
Residual Current Detection			Integrated		
Over Temperature Protection			Integrated		
DC Switch			Optional		
General Data					
Ambient temperature range			-25 ° C ~ +60 ° C		
Relative Humidity			0 ~ 95%		
Operating Altitude			< 2000m		
Dimensions (W / H / D)			380mm x 320mm x 140mm		
Weight	12 Kg	13 Kg	13 Kg	13 Kg	13 Kg
Mounting			Wall Bracket		
Topology			Transformerless		
Cooling Method			Natural convection		
Night Power Consumption			< 0.2 W		
Degree of Protection			IP65		
Noise Emission			< 30 dB		
Display			LCD 2 x 16 Characters		
Communication			GPRS / Wi-Fi / RS485 /Ethernet/WIFI/GPRS/USB		
Warranty			Standard 5 years 10/15/20/25 years extension optional		
Certifications & Standards					
Grid Regulation	VDE AR-N-4105, VDE 0126-1-1+A1, AS4777, CEI021, G83/1, G83/2, G59/2, G59/3, RD1663, IEC61727, UTE C15-712, MEA, PEA, EN50438,IEC61727				
Safety	IEC62109-1, IEC62109-2, AS/NZS3100				
EMC	IEC61000-6-2, IEC61000-6-3, AS/NZS3100				

UWAGA: Zdjęcie poglądowe dla całej rodziny produktów.